

+ H.264 Standalone DVR +



▶ CLICK IMAGE TO VIEW

▶ FEATURE

- H.264 Codec Built-in
- Real-Time Display
- Friendly GUI
- USB(2.0) Support & Mouse Control
- Remote Access & Control
- RS-485 for PTZ Control
- Embedded Linux
- Watermark & Data Protection
- DDNS Support
- Events Notification to Email or PC Client
- Pentaplex
- Monitoring, Recording, Playback, Network, Back-Ups

▶ MANUAL

▶ DIMENSION

▶ DEMO PLAY

↓ DOWNLOAD MORE ▶

▶ SPECIFICATIONS

Specification		CQ-400	CQ-800	CQ1600	
Video Input		4CH	8CH	16CH	
Monitor Output		1 BNC, 1 VGA, 1 SPOT			
Display Speed	NTSC	120 fps	240 fps	480 fps	
	PAL	100 fps	200 fps	400 fps	
Compression		H.264			
Recording Speed	NTSC	Resolution	720x480 @D1, 720x240 @Half-D1, 360x240 @CIF		
		Quality	High, Middle, Low	High, Middle, Low	High, Middle, Low
		Mode	Normal, Motion, Alarm	Normal, Motion, Alarm	Normal, Motion, Alarm
	PAL	Resolution	720x576 @D1, 720x2880 @Half-D1, 360x288 @CIF		
		Quality	High, Middle, Low	High, Middle, Low	High, Middle, Low
		Mode	Normal, Motion, Alarm	Normal, Motion, Alarm	Normal, Motion, Alarm
OS		Embedded Linux			
Pentaplex		Live, Recording, Playback, Network, Backup			
Sensor Input / Alarm Output		1Ch / 1Ch			
Audio		1Ch			
Display Mode		1CH / 4CH	1CH / 4CH / 8CH	1CH / 4CH / 8CH / 16CH	
System Control		IR Remote Control & Mouse Support			
Search Mode		Date & Time, Calender, Event(Alarm, Motion, Audio)			
PTZ Control		RS-485			
Back-Ups		External HDD, CD & DVR RW, Network, Memory Stick			
HDD Storage		1 HDD(Max.)			
Network		Remote Client, Internet Explorer, CMS			
Remote Monitoring S/W		CMS, Email Notification, Web Viewer			
Watermark		Algorithm			
Protocol		TCP/IP, SMTP, HTTP, DHCP, PPPOE(ADSL)			
Serial Communication		RS-232C 1EA & RS-485 1EA			
Application		Windows 2000, XP(Client PC), Windows VISTA			
Web Browser		Internet Explorer 5.0 or Higher			
Power Consumption		DC12V / 3A			
Dimension		435(W)mm x 425(D)mm x 87(H)mm			
Weight		3.5 Kg(Gross)			